



MATERIAL SAFETY DATA SHEET SDS/MSDS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : **Chromium Trioxide**

CAS-No. : 1333-82-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

1.3 Details of the supplier of the safety data sheet

Company :Bio-Chem Chemicals
5455 Nicholson Road, Science Market
Ambala Cantt, 133001 - Haryana
+91 82952 41953
info@biofinechemical.com - www.biofinechemical.com

1.4 Emergency telephone number

Emergency Phone # +91 99921 51495 (10.00am - 06.30pm) (Office Hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Oxidizing solids (Category 1), H271
Acute toxicity, Oral (Category 3), H301
Acute toxicity, Inhalation (Category 2), H330
Acute toxicity, Dermal (Category 3), H311
Skin corrosion (Category 1A), H314
Respiratory sensitization (Category 1), H334
Skin sensitization (Category 1), H317
Germ cell mutagenicity (Category 1B), H340
Carcinogenicity (Category 1A), H350
Reproductive toxicity (Category 2), H361f
Specific target organ toxicity - repeated exposure (Category 1), H372
Acute aquatic toxicity (Category 1), H400
Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H271

May cause fire or explosion; strong oxidizer.

H301 + H311

Toxic if swallowed or in contact with skin

H314

Causes severe skin burns and eye damage.

H317

May cause an allergic skin reaction.

H330

Fatal if inhaled.

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H340

May cause genetic defects.

H350

May cause cancer.

H361f

Suspected of damaging fertility.

H372

Causes damage to organs through prolonged or repeated exposure.

H410

Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P201

Obtain special instructions before use.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284

Wear respiratory protection.

P301 + P310 + P330

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

P371 + P380 + P375

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

Supplemental Hazard Statements

none

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Chromic anhydride

Formula : CrO₃

Molecular weight : 99.99 g/mol

CAS-No. : 1333-82-0

EC-No. : 215-607-8

Index-No. : 024-001-00-0

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
Chromium (VI) oxide Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)		
CAS-No.	1333-82-0	Ox. Sol. 1; Acute Tox. 3; Acute
EC-No.	215-607-8	Tox. 2; Acute Tox. 3; Skin
Index-No.	024-001-00-0	Corr. 1A; Resp. Sens. 1; Skin
		Sens. 1; Muta. 1B; Carc. 1A;
		Repr. 2; STOT RE 1; Aquatic
		Acute 1; Aquatic Chronic 1;
		H271, H301, H330, H311,
		H314, H334, H317, H340,
		H350, H361f, H372, H400,
		H410
		Concentration limits:
		>= 1 %: STOT SE 3, H335;
		M-Factor - Aquatic Acute: 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician. **In case of skin contact**

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Chromium oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Avoid exposure - obtain special instructions before use.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

hygroscopic Heat sensitive.

Storage class (TRGS 510): Strongly oxidizing hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If the full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a) Appearance	Form: crystalline Colour: violet
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: 196 °C - dec.
f) Initial boiling point and boiling range	No data available
g) Flash point	Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	2.700 g/cm ³
n) Water solubility	1.667 g/l - soluble
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	The substance or mixture is classified as oxidizing with the category 1.

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat Avoid moisture.

10.5 Incompatible materials

Organic materials, Phosphorus, Powdered metals

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Chromium oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 52 mg/kg(Chromium (VI) oxide)

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male - 4 h - 217 mg/m³(Chromium (VI) oxide)

LD50 Dermal - Rabbit - male and female - 57 mg/kg(Chromium (VI) oxide)

(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit(Chromium (VI) oxide)

Result: Corrosive - 24 h

Serious eye damage/eye irritation

Eyes - Rabbit(Chromium (VI) oxide)

Result: Corrosive to eyes

Respiratory or skin sensitisation

No data available(Chromium (VI) oxide)

Germ cell mutagenicity

May alter genetic material.(Chromium (VI) oxide)

In vivo tests showed mutagenic effects(Chromium (VI) oxide)

Carcinogenicity

This is or contains a component that has been reported to be carcinogenic classification.(Chromium (VI) oxide)

Human carcinogen.(Chromium (VI) oxide)

IARC: 1 - Group 1: Carcinogenic to humans (Chromium (VI) oxide)

Reproductive toxicity

Suspected human reproductive toxicant(Chromium (VI) oxide)

May cause reproductive disorders.(Chromium (VI) oxide)

Specific target organ toxicity - single exposure

No data available(Chromium (VI) oxide)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available(Chromium (VI) oxide)

Additional Information

RTECS: GB6650000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea(Chromium (VI) oxide)

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

LC50 - Tilapia mossambica - 21.05 - 141.38 mg/l - 96.0 h(Chromium (VI) oxide)

LC0 - Leuciscus idus (Golden orfe) - 100 mg/l - 48.0 h(Chromium (VI) oxide)

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 0.8 mg/l - 48 h(Chromium (VI) oxide)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available (Chromium (VI) oxide)

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1463

IMDG: 1463

IATA: 1463

14.2 UN proper shipping name

ADR/RID: CHROMIUM TRIOXIDE, ANHYDROUS

IMDG: CHROMIUM TRIOXIDE, ANHYDROUS

IATA: Chromium trioxide, anhydrous

14.3 Transport hazard class(es)

ADR/RID: 5.1 (6.1, 8)

IMDG: 5.1 (6.1, 8)

IATA: 5.1 (6.1, 8)

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H271 May cause fire or explosion; strong oxidizer.

H301 Toxic if swallowed.

H301 + H311 Toxic if swallowed or in contact with skin

H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product.