

PETROLEUM ETHER 40-60°C AR MSDS

CAS-No.: 8032-32-4 MSDS



MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
:
EC Index-No. : 649-263-00-9
EC-No. : 232-453-7
CAS-No. : 8032-32-4
Product code : B-01132

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Bio-Chem Chemicals
5455, Nicholson Road Science Market,
Ambala Cantt. 133001 Haryana (India)
+91-82952 41953
info@biofinechemical.com - www.biofinechemical.com

1.4. Emergency telephone number

Emergency number : +91 99921 51495 (10.00am - 06.30pm) (Office Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H225
Category 2
Skin corrosion/irritation, H315
Category 2
Reproductive toxicity, H361
Category 2
Specific target organ H336
toxicity — Single
exposure, Category 3,
Narcosis
Specific target organ H373
toxicity — Repeated
exposure, Category 2
Aspiration hazard, H304
Category 1
Hazardous to the aquatic H411
environment — Chronic
Hazard, Category 2

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

Full text of H statements : see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; N; Xn; Carc.Cat.2; Muta.Cat.2; R11-38-48/20-51/53-62-65-67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07



GHS08



GHS09

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapours, dust, fume, gas.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, face protection, eye protection.
P301+P310 - IF SWALLOWED: Immediately call a doctor.
P331 - Do NOT induce vomiting.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Name : PETROLEUM ETHER 40-60°C AR
CAS-No. : 8032-32-4
EC-No. : 232-453-7
EC Index-No. : 649-263-00-9

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

Full text of R- and H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of water/.... Wash contaminated clothing before reuse. Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Immediately call a POISON CENTER/doctor. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause genetic defects. May cause cancer. Causes damage to organs.
- Symptoms/effects after inhalation : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.
- Unsuitable extinguishing media : Do not use extinguishing media containing water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Use personal protective equipment as required.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : On land, sweep or shovel into suitable containers. Collect spillage.

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapours. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions	: Keep in fireproof place. Keep container tightly closed.
Incompatible materials	: Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Hand protection	: Protective gloves
Eye protection	: Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: [In case of inadequate ventilation] wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Clear Colorless.
Odour	: gasoline or kerosene.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: 10
Melting point	: < -73 °C
Freezing point	: No data available

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

Boiling point	: 40 - 60 °C
Flash point	: -40 °C
Auto-ignition temperature	: 288 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable Highly flammable liquid and vapour.
Vapour pressure	: 40 mm Hg at 20°C
Relative vapour density at 20 °C	: 2.5
Relative density	: No data available
Density	: 0.60 - 0.75
Solubility	: Water: Insoluble in water
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.011 - 0.059 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Heat. Sparks.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

PETROLEUM ETHER 40-60°C AR (8032-32-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

14.1. UN number	
UN-No. (ADR)	: 1268
UN-No. (IMDG)	: 1268
UN-No. (IATA)	: 1268
UN-No. (ADN)	: 1268
UN-No. (RID)	: 1268
14.2. UN proper shipping name	
Proper Shipping Name (ADR)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IATA)	: Petroleum distillates, n.o.s.
Proper Shipping Name (ADN)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (RID)	: PETROLEUM DISTILLATES, N.O.S.
Transport document description (ADR)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 1268 Petroleum distillates, n.o.s., 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)	
ADR	
Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3
	:
IMDG	
Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3
	:
IATA	
Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3
	:
ADN	
Transport hazard class(es) (ADN)	: 3

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 640C, 363, 664

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T7

Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28

Tank code (ADR) : L1.5BN

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Orange plates :

Tunnel restriction code (ADR) : D/E

EAC code : 3YE

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

- Transport by sea

Special provisions (IMDG)	: 363
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
MFAG-No	: 128

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3H

- Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 363, 640C
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 363, 640C
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

PETROLEUM ETHER 40-60°C AR is not on the REACH Candidate List

PETROLEUM ETHER 40-60°C AR is not on the REACH Annex XIV List

15.1.2. National regulations

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to AwSV; ID No. 9162)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : PETROLEUM ETHER 40-60°C AR is listed

SZW-lijst van mutagene stoffen : PETROLEUM ETHER 40-60°C AR is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-statements:

PETROLEUM ETHER 40-60°C AR

Safety Data Sheet

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
F	Highly flammable

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product