

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifiers

Product name : Vinyl Acetate

CAS-No. : 108-05-4

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Industrial & for professional use only.

### 1.3 Details of the supplier of the safety data sheet

Company : Bio-Chem Chemicals  
5455 Nicholson Road, Science Market  
Ambala Cantt, 133001 - Haryana  
+91 82952 41953  
info@biofinechemical.com - www.biofinechemical.com

### 1.4 Emergency telephone number

Emergency Phone # : +91 99921 51495 (10.00am - 06.30pm) (Office Hours)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Acute toxicity, Inhalation (Category 4), H332

Carcinogenicity (Category 2), H351

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Chronic aquatic toxicity (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 Label elements

#### Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H332

Harmful if inhaled.

H335

May cause respiratory irritation.

H351

Suspected of causing cancer.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273	Avoid release to the environment.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P403 + P235	Store in a well-ventilated place. Keep cool.
Supplemental Hazard Statements	none

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Synonyms : Acetoxyethylene

Formula : C<sub>4</sub>H<sub>6</sub>O<sub>2</sub>  
Molecular weight : 86.09 g/mol  
CAS-No. : 108-05-4  
EC-No. : 203-545-4  
Index-No. : 607-023-00-0

#### Hazardous ingredients according to Regulation (EC) No 1272/2008

Component		Classification	Concentration
<b>Vinyl acetate</b>			
CAS-No.	108-05-4	Flam. Liq. 2; Acute Tox. 4;	<= 100 %
EC-No.	203-545-4	Carc. 2; STOT SE 3; Aquatic	
Index-No.	607-023-00-0	Chronic 3; H225, H332, H351, H335, H412	

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### **5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

### **5.3 Advice for firefighters**

Wear self-contained breathing apparatus for firefighting if necessary.

### **5.4 Further information**

Use water spray to cool unopened containers.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

### **6.2 Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

### **6.3 Methods and materials for containment and cleaning up**

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

### **6.4 Reference to other sections**

For disposal see section 13.

## **SECTION 7: Handling and storage**

### **7.1 Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

### **7.2 Conditions for safe storage, including any incompatibilities**

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature 2 - 8 °C

Storage class (TRGS 510): Flammable liquids

### **7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

### **8.2 Exposure controls**

#### **Appropriate engineering controls**

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### **Personal protective equipment**

##### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

**Skin protection**

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (US) or type ABEK (EN 14387) respirator cartridges as a backup to enginee protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

**Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid, clear Colour: colourless
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	Melting point/range: -93 °C - lit.
f) Initial boiling point and boiling range	72 - 73 °C - lit.
g) Flash point	-8 °C - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 13.4 %(V) Lower explosion limit: 2.6 %(V)
k) Vapour pressure	No data available
l) Vapour density	2.97 - (Air = 1.0)
m) Relative density	0.934 g/cm <sup>3</sup> at 25 °C
n) Water solubility	20 g/l at 20 °C
o) Partition coefficient: n-octanol/water	log Pow: 3.0
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

## 9.2 Other safety information

Relative vapour density 2.97 - (Air = 1.0)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Unstable upon depletion of inhibitor.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

acids, Bases, Oxidizing agents, Peroxides

### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 2,900 mg/kg(Vinyl acetate)

LC50 Inhalation - Rat - 4 h - 14.1 mg/l(Vinyl acetate)

LD50 Dermal - Rabbit - 2,335 mg/kg(Vinyl acetate)

LD50 Dermal - Rabbit - 7,440 mg/kg(Vinyl acetate)

#### Skin corrosion/irritation

Skin - Rabbit(Vinyl acetate)

Result: No skin irritation

(OECD Test Guideline 404)

#### Serious eye damage/eye irritation

Eyes - Rabbit(Vinyl acetate)

Result: No eye irritation

(OECD Test Guideline 405)

#### Respiratory or skin sensitisation

in vivo assay - Mouse(Vinyl acetate)

Does not cause skin sensitisation.

(OECD Test Guideline 429)

#### Germ cell mutagenicity

in vitro assay(Vinyl acetate)

lymphocyte

Result: Equivocal evidence.

Chromosome aberration test in vitro(Vinyl acetate)

Other cell types

Result: positive

Result: Not mutagenic in Ames Test

#### Carcinogenicity

Carcinogenicity- Rat- Inhalation(Vinyl acetate)

Limited evidence of carcinogenicity in animal studies(Vinyl acetate)

(Vinyl acetate)

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Vinyl acetate)

**Reproductive toxicity**

No data available(Vinyl acetate)

**Specific target organ toxicity - single exposure**

Inhalation - May cause respiratory irritation.(Vinyl acetate)

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available(Vinyl acetate)

**Additional Information**

RTECS: AK0875000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Vinyl acetate)

**SECTION 12: Ecological information****12.1 Toxicity**

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 14 mg/l - 96 h(Vinyl acetate)

NOEC - Pimephales promelas (fathead minnow) - 0.16 mg/l - 28 d(Vinyl acetate)  
(OECD Test Guideline 212)

Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 12.6 mg/l - 48 h(Vinyl acetate)  
(OECD Test Guideline 202)

Toxicity to algae NOEC - Pseudokirchneriella subcapitata (green algae) - 1.58 mg/l - 96 h(Vinyl acetate)  
(OECD Test Guideline 201)  
EC50 - Pseudokirchneriella subcapitata (green algae) - 12.7 mg/l - 96 h(Vinyl acetate)  
(OECD Test Guideline 201)

**12.2 Persistence and degradability**

Biodegradability Result: 82 - 98 % - Readily biodegradable.  
(OECD Test Guideline 301C)

**12.3 Bioaccumulative potential**

No bioaccumulation is to be expected (log Pow <= 4).

**12.4 Mobility in soil**

No data available(Vinyl acetate)

**12.5 Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**12.6 Other adverse effects**

Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable.  
Offer surplus and non-recyclable solutions to a licensed disposal company.

**Contaminated packaging**

Dispose of as unused product.

## SECTION 14: Transport information

### 14.1 UN number

ADR/RID: 1301

IMDG: 1301

IATA: 1301

### 14.2 UN proper shipping name

ADR/RID: VINYL ACETATE, STABILIZED

IMDG: VINYL ACETATE, STABILIZED

IATA: Vinyl acetate, stabilized

### 14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

### 14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

### 14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

### 14.6 Special precautions for user

No data available

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

### 15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.