



MATERIAL SAFETY DATA SHEET SDS/MSDS

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WANKLYN SOAP SOLUTION

OTHER NAMES**PROPER SHIPPING NAME**

FLAMMABLE LIQUID, N.O.S.

PRODUCT USE

Test reagent. Used as per manufacturers directions.

SUPPLIER

Company: Bio-Chem Chemicals


Address:

5455 Nicholson Road, Science Market

Ambala Cantt, 133001 - Haryana

+91 82952 41953

info@biofinechemical.com - www.biofinechemical.com

HAZARD RATINGS

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Eye Irritation Category 2A

Flammable Liquid Category 2

Respiratory Effects Category 3

Respiratory Irritation Category 3

Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H335 H336 H225 H316 H319

May cause respiratory irritation

May cause drowsiness and dizziness

Highly flammable liquid and vapour

Causes mild skin irritation

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Use only non-sparking tools.

Take precautionary measures against static discharge

Wash hands thoroughly after handling.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment

Keep away from heat/sparks/open flame - No smoking.

Keep container tightly closed.

Wear protective gloves and eye/face protection.

Response

If skin irritation occurs, seek medical advice/attention.

If eye irritation persists, get medical advice/attention.

Wear eye/face protection.

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ethanol	64-17-5	>60
water	7732-18-5	N/S

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

-
- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

For acute or short term repeated exposures to ethanol:

- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- Fructose administration is contra-indicated due to side effects.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.

-
- BCF (where regulations permit).
 - Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Other combustion products include: carbon dioxide (CO₂).

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

ethanol 3300 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

ethanol 3300 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

ethanol 3000 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

ethanol 1000 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

Avoid generating and breathing mist.

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.

-
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Segregate from strong oxidisers peroxides and alkali metals e.g. sodium, potassium, lithium.
DO NOT store in aluminium containers.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



-
- +: May be stored together
O: May be stored together with specific preventions
X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- ethanol: CAS:64- 17- 5
- water: CAS:7732- 18- 5

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
ethanol		3, 300 [LEL]

NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

ODOUR SAFETY FACTOR (OSF)

OSF=6 (ETHANOL)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
-------	-----	-------------

A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

None assigned. Refer to individual constituents.

INGREDIENT DATA

ETHANOL:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects.

Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness.

Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes.

Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep.

At 15000 ppm there was continuous lachrymation and coughing.

WATER:

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure,

begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

· Barrier cream and Butyl rubber gloves or Wear chemical protective gloves, eg. PVC. Wear safety footwear.

OTHER

· Overalls.
· Eyewash unit.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid	2.5- 10 m/s (500- 2000 f/min.)

air motion).

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless to slight yellow liquid with alcohol odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: Not applicable

Melting Range (°C): Not available

Solubility in water (g/L): Miscible

pH (1% solution): Not available

Volatile Component (%vol): Not available

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not available

Autoignition Temp (°C): Not available

State: Liquid

Boiling Range (°C): 76

Specific Gravity (water=1): 0.90

pH (as supplied): Not available

Vapour Pressure (kPa): Not available

Evaporation Rate: Not available

Flash Point (°C): 21 (OC)

Upper Explosive Limit (%): Not available

Decomposition Temp (°C): Not available

Viscosity: Not available

log Kow (Sangster 1997):

- 0.3

log Kow: -0.31- -0.32

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Ingestion may result in nausea, abdominal irritation, pain and vomiting.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

The liquid may produce eye discomfort causing transient smarting, blinking.

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Contact with cuts, abraded skin is painful, but this is transient.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

INHALED

Inhalation may produce health damage*.

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by skin contact with the material, ingestion and inhalation of vapour.

Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following.

Ingestion may result in intoxication, drunkenness. In chronic form this may result in alcoholism, liver damage.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour,

accidental

mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

ETHANOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 7060 mg/kg
Oral (human) LDLo: 1400 mg/kg
Oral (man) TDLo: 50 mg/kg
Oral (man) TDLo: 1.40 mg/kg
Oral (woman) TDLo: 256 mg/kg/12 wks
Inhalation (rat) LC50: 20, 000 ppm/10h
Inhalation (rat) LC50: 64000 ppm/4h

IRRITATION

Skin (rabbit):20 mg/24hr- Moderate
Skin (rabbit):400 mg (open)- Mild
Eye (rabbit):100mg/24hr- Moderate
Eye (rabbit): 500 mg SEVERE

WATER:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant:Not Determined

Refer to data for ingredients, which follows:

ETHANOL:

Fish LC50 (96hr.) (mg/l):	13480
Algae IC50 (72hr.) (mg/l):	1450
log Kow (Sangster 1997):	- 0.3
BOD5:	63%
ThOD:	2.1
Half- life Soil - High (hours):	24
Half- life Soil - Low (hours):	2.6
Half- life Air - High (hours):	122
Half- life Air - Low (hours):	12.2
Half- life Surface water - High (hours):	26
Half- life Surface water - Low (hours):	6.5
Half- life Ground water - High (hours):	52
Half- life Ground water - Low (hours):	13
Aqueous biodegradation - Aerobic - High (hours):	26
Aqueous biodegradation - Aerobic - Low (hours):	6.5
Aqueous biodegradation - Anaerobic - High (hours):	104
Aqueous biodegradation - Anaerobic - Low (hours):	26
Aqueous biodegradation - Removal secondary treatment - High (hours):	67%
Photooxidation half- life water - High (hours):	3.20E+05
Photooxidation half- life water - Low (hours):	8020
Photooxidation half- life air - High (hours):	122
Photooxidation half- life air - Low (hours):	12.2

DO NOT discharge into sewer or waterways.

log Kow: -0.31- -0.32

Half-life (hr) air: 144

Half-life (hr) H2O surface water: 144

Henry's atm m³ /mol: 6.29E-06

BOD 5 if unstated: 0.93-1.67,63%

COD: 1.99-2.11,97%

ThOD: 2.1

When ethanol is released into the soil it readily and quickly biodegrades but may leach into ground water; most is lost by evaporation. When released into water the material readily evaporates and is biodegradable. Ethanol does not bioaccumulate to an appreciable extent. The material is readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
 - Consult State Land Waste Management Authority for disposal.
 - Incinerate residue at an approved site.
 - Recycle containers if possible, or dispose of in an authorised landfill.
-

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]E

UNDG:

Dangerous Goods Class: 3	Subrisk:	None
UN Number: 1993	Packing Group:	II
Shipping Name: FLAMMABLE LIQUID, N.O.S.		

Air Transport IATA:

ICAO/IATA Class: 3	ICAO/IATA Subrisk:	None
UN/ID Number: 1993	Packing Group:	II
Special provisions: A3		
Shipping Name: FLAMMABLE LIQUID N.O.S.		

Maritime Transport IMDG:

IMDG Class: 3	IMDG Subrisk:	None
UN Number: 1993	Packing Group:	II
EMS Number: F- E, S- E	Special provisions:	274 330 944
Marine Pollutant: Not Determined		
Shipping Name: FLAMMABLE LIQUID, N.O.S.		

Section 15 - REGULATORY INFORMATION

REGULATIONS

Hardness Soap Solution (CAS: None):
No regulations applicable

ethanol (CAS: 64-17-5) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
International Air Transport Association (IATA) Dangerous Goods Regulations

International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

water (CAS: 7732-18-5) is found on the following regulatory lists;
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

REPRODUCTIVE HEALTH GUIDELINES

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
ethanol	1880 mg/m ³	NA	NA	NA	Yes

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive
American Industrial Hygiene Association Journal 57: 641-649 (1996).