

MATERIAL SAFETY DATA SHEET SDS/MSDS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 **Product identifiers**

> : EUPAROL (MOUNTING MEDIA) FOR Product name

> > **MICROSCOPY**

B-01198 **Product Number** CAS No. 108-88-3 Bio-Chem Brand

Relevant identified uses of the substance or mixture and uses advised against 1.2

Identified uses : In vitro diagnostic reagent, Reagent for analysis : This product is not intended for consumer use. Uses advised against

Details of the supplier of the safety data sheet

Company : Bio-Chem Chemicals

5455 NicholsonRoad, Science Market Ambala Cantt, 133001 - Haryana +91 82952 41953

info@biofinechemical.com - www.biofinechemical.com

Emergency telephone 1.4

> : +91 99921 51495 (10.00am - 06.30pm) (Office Hours) Emergency Phone #

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

> Flammable liquids, (Category 2) H225: Highly flammable liquid and vapor.

Skin irritation, (Category 2) H315: Causes skin irritation.

Reproductive toxicity, (Category H361d: Suspected of damaging the unborn

child.

Specific target organ toxicity -H336: May cause drowsiness or dizziness.

single exposure, (Category 3), Central nervous system

2)

Specific target organ toxicity - repeated exposure, (Category 2),

Central nervous system

H373: May cause damage to organs through prolonged or repeated exposure if

inhaled.

Aspiration hazard, (Category 1)

H304: May be fatal if swallowed and enters

airways.

Long-term (chronic) aquatic

hazard, (Category 3)

H412: Harmful to aquatic life with long

lasting effects.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (Central nervous system) through

prolonged or repeated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P202 Do not handle until all safety precautions have been read and

understood.

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P273 Avoid release to the environment.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water.

P331 Do NOT induce vomiting.

Supplemental Hazard

Statements

none

Reduced Labeling (<= 125 ml)

Pictogram



Signal Word Danger

Hazard Statements

H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.
H361d Suspected of damaging the unborn child.

Precautionary Statements

P202 Do not handle until all safety precautions have been read and

understood.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Toluene CAS-No. 108-88-3 Flam. Liq. 2; Skin Irrit. 2; >= 70 -	_
CAS-No. 108-88-3 Flam. Lig. 2: Skin Irrit. 2: >= 70 -	
EC-No. 203-625-9 Repr. 2; STOT SE 3; STOT Registration 01-2119471310-51- number XXXX Registration 1436, H336, H373, H304, H412 Concentration limits: 20 %: STOT SE 3, H336;	< 90

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Dry powder Foam

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: Viton®

Minimum layer thickness: 0,7 mm Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0,7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic

compounds

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state liquid b) Color colorless c) Odor characteristic d) Melting No data available point/freezing point e) Initial boiling point No data available and boiling range Flammability (solid, No data available f) gas)

g) Upper/lower Upper explosion limit: 8 %(V) - Toluene flammability or explosive limits Upper explosion limit: 1,2 %(V) - Toluene

h) Flash point 8 °C

i) Autoignition No data available temperature

j) Decomposition No data available temperature

k) pH No data available

I) Viscosity Viscosity, kinematic: No data available Viscosity, dynamic: 60 - 100 mPa.s at 20 °C

m) Water solubility at 20 °C practically insoluble

n) Partition coefficient: No data available n-octanol/water

o) Vapor pressure No data available
p) Density No data available
Relative density No data available
q) Relative vapor No data available

density

r) Particle characteristics

No data available

- s) Explosive properties Not classified as explosive.
- t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with:

fuming sulfuric acid

Nitric acid

silver

perchlorates

nitrogen dioxide

halogen-halogen compounds

uranium hexafluoride

organic nitro compounds

nonmetallic halides

acetic acid

Violent reactions possible with:

Strong oxidizing agents

Strong acids

sulfur

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

Rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Oral: No data available Inhalation: No data available Dermal: No data available Skin corrosion/irritation

Remarks: Mixture causes skin irritation.

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

Evidence of harm to the unborn child.

Specific target organ toxicity - single exposure

Mixture may cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Mixture may cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Endocrine disrupting properties

Product:

The substance/mixture does not contain Assessment

> components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

Handle in accordance with good industrial hygiene and safety practice.

Components

Toluene

Acute toxicity

LD50 Oral - Rat - male - 5.580 mg/kg (Directive 67/548/EEC, Annex V, B.1.)

LC50 Inhalation - Rat - male - 4 h - 25,7 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male - > 5.000 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: irritating - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Result: negative Test Type: Ames test

Test system: S. typhimurium

Result: negative

Species: Rat - Bone marrow

Result: negative Remarks: (ECHA)

Carcinogenicity

No data available

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

: The substance/mixture does not contain components Assessment

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Discharge into the environment must be avoided.

Components

Toluene

flow-through test LC50 - Oncorhynchus kisutch (coho salmon) -Toxicity to fish

> 5,5 mg/l - 96 h Remarks: (ECHA)

Toxicity to daphnia

EC50 - Ceriodaphnia dubia (water flea) - 3,78 mg/l - 48 h (US-EPA)

and other aquatic invertebrates

static test EC50 - Bacteria - 84 mg/l - 24 h Toxicity to bacteria

Remarks: (ECHA)

Toxicity to

flow-through test NOEC - Oncorhynchus kisutch (coho salmon)

fish(Chronic toxicity) - 1,39 mg/l - 40 d

Remarks: (ECHA)

Toxicity to daphnia

and other aquatic

invertebrates(Chronic

toxicity)

NOEC - Ceriodaphnia dubia (water flea) - 0,74 mg/l - 7 d

(US-EPA)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

IMDG: 1866 IATA: 1866 ADR/RID: 1866

14.2 UN proper shipping name

ADR/RID: RESIN SOLUTION

IMDG: RESIN SOLUTION IATA: Resin solution

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, : Toluene placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

National legislation

Seveso III: Directive 2012/18/EU of the P5c FLAMMABLE LIQUIDS European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if